SAFETY DATA SHEET

1. Identification

Product identifier Liquid Wrench Penetrating Oil

Other means of identification

SDS number L112

Part No. L106, L112 3403.19.5000 Tariff code Penetrating Oil Recommended use **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **RSC Chemical Solutions Address** 600 Radiator Road

Indian Trail, NC 28079 **United States**

Customer Service: (704) 821-7643 **Telephone**

> Technical: (704) 684-1811

Website www.rscbrands.com E-mail sds@rscbrands.com

Emergency Telephone: **Emergency phone number** (303) 623-5716

> RMPDC (877-740-5015) **Emergency Contact:**

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2 Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

hazard

Hazardous to the aquatic environment, acute Category 2

Hazardous to the aquatic environment,

long-term hazard

Category 2

Not classified. **OSHA** defined hazards

Label elements

Environmental hazards



Signal word Danger

Hazard statement Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting

effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the

environment. Wear eye protection/face protection. Wear protective gloves.

Material name: Liquid Wrench Penetrating Oil

IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously Response

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect

spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Combustible.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	70 - < 80
1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, Hydrogenated		1581740-29-5	5 - < 10
Carbon Dioxide		124-38-9	1 - < 3
Other components below reportable le	evels		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if **Eve contact**

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CF	FR 1910.1000)	
---	---------------	--

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
,		5000 ppm
US. ACGIH Threshold Limit Value	es	
Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
,	TWA	5000 ppm
US. NIOSH: Pocket Guide to Cher	nical Hazards	
Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3
,		30000 ppm
	TWA	9000 mg/m3
		5000 ppm
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	100 mg/m3

Material name: Liquid Wrench Penetrating Oil

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Wear appropriate chemical resistant gloves. Hand protection Other Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with

organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Liquid Opaque **Appearance**

Liquid. Physical state **Form** Aerosol. Color Yellow Odor Fragrance Not available. Odor threshold Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

range

347 °F (175 °C) estimated

200.0 °F (93.3 °C) Tag Closed Cup Flash point

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

8.5 % estimated

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

0.51 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

410 °F (210 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Viscosity Not available.

Other information

7.26 lbs/gal Density **Explosive properties** Not explosive. Flame extension > 18 in Flammability (flash back) No

Flammability class Combustible IIIB estimated

Heat of combustion (NFPA

30B)

Oxidizing properties Not oxidizing.

Percent volatile 0.29 % estimated

Specific gravity 0.87 VOC 0 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

36.35 kJ/g

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May

cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Test Results Components **Species**

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, 6.08 - 6.48 OECD 117, Log Kow

Hydrogenated

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number Not available.

UN proper shipping name Consumer Commodity

Transport hazard class(es)

Class ORM-D

Subsidiary risk

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306 None Packaging non bulk Packaging bulk None

IATA

UN1950 **UN number**

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

L106, L112 Version #: 08 Revision date: 11-16-2016 Issue date: 04-27-2015

2.1 Class Subsidiary risk

Not applicable. Packing group

Environmental hazards Yes **ERG Code** 101

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Liquid Wrench Penetrating Oil

^{*} Estimates for product may be based on additional component data not shown.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable, MARINE POLLUTANT

Not established.

Transport hazard class(es)

2.1 **Class** Subsidiary risk

Not applicable. Packing group

Environmental hazards

Marine pollutant Yes F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Inventory name

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 04-27-2015

 Revision date
 11-16-2016

Version # 08
HMIS® ratings He

United States & Puerto Rico

Health: 2 Flammability: 1

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

NFPA ratings



Material name: Liquid Wrench Penetrating Oil

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

SDS US

L106, L112 Version #: 08 Revision date: 11-16-2016 Issue date: 04-27-2015